

MaxCeram 100 CERAMIC REPAIR PASTE BASE

Page: 1

Compilation date: 27/04/2016

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: MaxCeram 100 CERAMIC REPAIR PASTE BASE

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: MaxKote

Sherburn in Elmet Leeds North Yorkshire LS256BH United Kingdom Tel: 01977 682 903 Email: info@MaxKote.co.uk

1.4. Emergency telephone number

Emergency tel: 01977 682 903

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP:	Xi: R36/38; Sens.: R43; N: R51/53			
Classification under CLP:	Acute Tox. 4: H302; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin			
	Sens. 1: H317; -: EUH205			
Most important adverse effects:	Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic			
	organisms, may cause long-term adverse effects in the aquatic environment.			

2.2. Label elements

Label elements:		
Hazard statements:	EUH205: Contains epoxy constituents. May produce an allergic reaction.	
	H302: Harmful if swallowed.	
	H315: Causes skin irritation.	
	H317: May cause an allergic skin reaction.	
	H319: Causes serious eye irritation.	
	H411: Toxic to aquatic life with long lasting effects.	
Signal words:	Warning	
Hazard pictograms:	GHS07: Exclamation mark	
	GHS09: Environmental	[cc

MaxCeram 100 CERAMIC REPAIR PASTE BASE

Page: 2



Precautionary statements: P264: Wash skin thoroughly after handling.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.

P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P321: Specific treatment (see information on this label).

P501: Dispose of contents/container to hazardous or special waste collection point.

Label elements under CHIP:

Hazard symbols: Irritant.

Dangerous for the environment.

×	¥
---	---

Risk phrases:R36/38: Irritating to eyes and skin.R43: May cause sensitisation by skin contact.R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
environment.Safety phrases:S2: Keep out of the reach of children.
S24: Avoid contact with skin.
S29: Do not empty into drains.
S37: Wear suitable gloves.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS CAS	CHIP Classification	CLP Classification	Percent
------------	---------------------	--------------------	---------

MaxCeram 100 CERAMIC REPAIR PASTE BASE

Page: 3

500-033-5	25068-38-6	Xi: R36/38; Sens.: R43; N: R51/53	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%
BISPHENOL F	TYPE EPOXY R	ESIN		
500-108-2	28064-14-4	Xi: R36/38; N: R51/53; Sens.: R43	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Not applicable.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Dry chemical powder. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

MaxCeram 100 CERAMIC REPAIR PASTE BASE

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method. Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Avoid incompatible materials and conditions - see section 10 of SDS.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area.Respiratory protection:Respiratory protection not required.Hand protection:Protective gloves.Eye protection:Safety glasses.Skin protection:Impermeable protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

 State:
 Paste

 Colour:
 Dark grey

 Odour:
 Barely perceptible odour

 Evaporation rate:
 Negligible

MaxCeram 100 CERAMIC REPAIR PASTE BASE

Oxidising: Non-oxidising (by EC criteria) Solubility in water: Insoluble Viscosity: Highly viscous Boiling point/range°C: >200 Flash point°C: >150

Relative density: 2.6g/cc

Page: 5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Flames.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong oxidising agents. Amines. Alkalis.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route Species		Test	Value	Units	
ORAL	RAT	LD50	>2000	mg/kg	
ORAL	RBT	LD50	>2000	mg/kg	

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg

MaxCeram 100 CERAMIC REPAIR PASTE BASE

							Page:
SKN	RBT		LD50		>20	ml/kg	
Relevant effects for mixture:							
Effect		Route	e		Basis		
Irritation		OPT DF	RM	Hazardou	s: calculated		
Sensitisation		DRM		Hazardous	s: calculated		
mptoms / routes of exposur	e						
Skin contact:	There may be	mild irritatio	n at the site	of contact.			
Eye contact:	There may be	irritation and	d redness.				
Ingestion:	There may be	irritation of t	he throat.				
	-		he throat wit	h a feeling	of tightness in the cl	nest.	
elayed / immediate effects:	Not applicable	•					
ion 12: Ecological informa	ation						
2.1. Toxicity							
Ecotoxicity values:							
Speci	es		Tes	st	Value	Units	
FISH			96H LC50		>5000	mg/l	
2.2. Persistence and degrada	bility						
		ahla					
sistence and degradability:	•	able.					
2.3. Bioaccumulative potentia							
Bioaccumulative potential:	Bioaccumulati	on potential.					
2.4. Mobility in soil							
Mobility:	Insoluble in wa	ater.					
.5. Results of PBT and vPvB	assessment						
PBT identification:	This product is	s not identifie	ed as a PBT/	vPvB subs	stance.		
.6. Other adverse effects							
Other adverse effects:	: Toxic to aquatic organisms.						
ion 13: Disposal consider	ations						
3.1. Waste treatment methods	5						
Disposal operations:	Transfer to a s	uitable cont	ainer and arı	range for c	collection by specialis	ed disposal	
-				-	e disposed as solid v	-	
Waste code number:	08 04 09						
Disposal of packaging:	Dianaga of in a	n rogulated l	andfill aita ar	other med	had for bozardaus a	tovio wootoo	

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

MaxCeram 100 CERAMIC REPAIR PASTE BASE

Marine pollutant: No

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3077

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: Yes

14.6. Special precautions for user

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH205: Contains epoxy constituents. May produce an allergic reaction.
	H302: Harmful if swallowed.
	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
	H411: Toxic to aquatic life with long lasting effects.
	R36/38: Irritating to eyes and skin.

MaxCeram 100 CERAMIC REPAIR PASTE BASE

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.