

**SAFETY DATA SHEET**

MaxMet 100 METAL REPAIR PASTE ACTIVATOR

Page: 1

Compilation date: 12/05/2016

Revision No: 2

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** MaxMet 100 METAL REPAIR PASTE ACTIVATOR

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

**Company name:** MaxKote

Sherburn in Elmet

Leeds  
North Yorkshire  
LS256BH

United Kingdom

**Tel:** 01977 682 903

**Email:** [info@MaxMet.co.uk](mailto:info@MaxMet.co.uk)

**1.4. Emergency telephone number**

**Emergency tel:** 01977 682 903

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CHIP:** Xn: R20/21/22; C: R34; Sens.: R43; Xn: R68

**Classification under CLP:** Acute Tox. 4: H302; Muta. 2: H341; Repr. 2: H361f; Skin Corr. 1B: H314; Skin Sens. 1: H317

**Most important adverse effects:** Harmful by inhalation, in contact with skin and if swallowed. Causes burns. May cause sensitisation by skin contact. Possible risk of irreversible effects.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H341: Suspected of causing genetic defects.

H361f: Suspected of damaging fertility.

**Signal words:** Danger

**Hazard pictograms:** GHS05: Corrosion

GHS07: Exclamation mark

GHS08: Health hazard

[cont...]

# SAFETY DATA SHEET

MaxMet 100 METAL REPAIR PASTE ACTIVATOR



**Precautionary statements:** P102: Keep out of reach of children.  
P202: Do not handle until all safety precautions have been read and understood.  
P260: Do not breathe dust/fumes/gas/mist/vapours/spray.  
P301+312: IF SWALLOWED: Call a POISON CENTER/doctor/ if you feel unwell.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P501: Dispose of contents/container to hazardous or special waste collection point.

## Label elements under CHIP:

**Hazard symbols:** Corrosive.



**Risk phrases:** R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.  
R34: Causes burns.  
R43: May cause sensitisation by skin contact.  
R68: Possible risk of irreversible effects.

**Safety phrases:** S1/2: Keep locked up and out of the reach of children.  
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.  
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

**Hazardous ingredients:**

# SAFETY DATA SHEET

MaxMet 100 METAL REPAIR PASTE ACTIVATOR

## FORMALDEHYDE POLYMER WITH PHENOL AND TETA

EINECS	CAS	CHIP Classification	CL P Classification	Percent
-	32610-77-8	Xn: R21/22; C: R34; Sens.: R43; -: R52/53	-	10-30%

## 2,2'-IMINODIETHYLAMINE

203-865-4	111-40-0	Xn: R21/22; C: R34; Sens.: R43	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317	1-10%
-----------	----------	--------------------------------	---	-------

## 4,4'-ISOPROPYLIDENEDIPHENOL

201-245-8	80-05-7	Xn: R62; Xi: R37; Xi: R41; Sens.: R43; -: R52	Repr. 2: H361f; STOT SE 3: H335; Eye Dam. 1: H318; Skin Sens. 1: H317	1-10%
-----------	---------	---	---	-------

## 3,6-DIAZAOCTANETHYLENEDIAMINE

203-950-6	112-24-3	Xn: R21; C: R34; Sens.: R43; -: R52/53	Acute Tox. 4: H312; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412	1-10%
-----------	----------	--	--	-------

## PHENOL

203-632-7	108-95-2	T: R23/24/25; C: R34; Xn: R48/20/21/22; Xn: R68	Muta. 2: H341; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Skin Corr. 1B: H314	1-10%
-----------	----------	---	---	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

**Eye contact:** Corneal burns may occur. May cause permanent damage.

[cont...]

# SAFETY DATA SHEET

MaxMet 100 METAL REPAIR PASTE ACTIVATOR

**Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Corrosive. In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Do not create dust.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of dust in the air.

[cont...]

# SAFETY DATA SHEET

MaxMet 100 METAL REPAIR PASTE ACTIVATOR

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

## 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

#### 2,2'-IMINODIETHYLAMINE

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	4.3 mg/m <sup>3</sup>	-	-	-

#### 4,4'-ISOPROPYLIDENEDIPHENOL

UK	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	-	-
----	---------------------	---------------------	---	---

#### PHENOL

UK	2 ppm	4 ppm	-	-
----	-------	-------	---	---

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

**Hand protection:** Protective gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Paste

**Colour:** Pale grey

**Odour:** Ammoniacal

**Relative density:** 1.70

# SAFETY DATA SHEET

MaxMet 100 METAL REPAIR PASTE ACTIVATOR

## 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### 2,2'-IMINODIETHYLAMINE

IPR	RAT	LD50	74	mg/kg
ORL	MUS	LD50	970	mg/kg
ORL	RAT	LD50	970	mg/kg
<b>4,4'-ISOPROPYLIDENEDIPHENOL</b>				
ORL	MUS	LD50	2400	mg/kg
ORL	RAT	LD50	3250	mg/kg

#### 3,6-DIAZAOCTANETHYLENEDIAMINE

IVN	MUS	LD50	350	mg/kg
ORL	MUS	LD50	1600	mg/kg

# SAFETY DATA SHEET

MaxMet 100 METAL REPAIR PASTE ACTIVATOR

ORL	RAT	LD50	2500	mg/kg
-----	-----	------	------	-------

## PHENOL

ORL	MUS	LD50	270	mg/kg
ORL	RAT	LD50	317	mg/kg
SCU	RAT	LD50	460	mg/kg

### Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM ING	Hazardous: calculated
Corrosivity	OPT INH DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

**Eye contact:** Corneal burns may occur. May cause permanent damage.

**Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

[cont...]

# SAFETY DATA SHEET

MaxMet 100 METAL REPAIR PASTE ACTIVATOR

## 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1759

### 14.2. UN proper shipping name

**Shipping name:** CORROSIVE SOLID, N.O.S.

### 14.3. Transport hazard class(es)

**Transport class:** 8

### 14.4. Packing group

**Packing group:** III

### 14.5. Environmental hazards

**Environmentally hazardous:** No

**Marine pollutant:** No

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** E

**Transport category:** 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H301: Toxic if swallowed.

H302: Harmful if swallowed.



# SAFETY DATA SHEET

## MaxMet 100 METAL REPAIR PASTE ACTIVATOR

H311: Toxic in contact with skin.  
H312: Harmful in contact with skin.  
H314: Causes severe skin burns and eye damage.  
H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.  
H331: Toxic if inhaled.  
H335: May cause respiratory irritation.  
H341: Suspected of causing genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H361f: Suspected of damaging fertility.  
H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H412: Harmful to aquatic life with long lasting effects.  
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.  
R21/22: Harmful in contact with skin and if swallowed.  
R21: Harmful in contact with skin.  
R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.  
R34: Causes burns.  
R37: Irritating to respiratory system.  
R41: Risk of serious damage to eyes.  
R43: May cause sensitisation by skin contact.  
R48/20/21/22: Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.  
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R52: Harmful to aquatic organisms.  
R62: Possible risk of impaired fertility.  
R68: Possible risk of irreversible effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.