

## SAFETY DATA SHEET

MAXCERAM 400 – HEAVY DUTY EPOXY CERAMIC  
REBUILDING COMPOUND ACTIVATOR BASE

Page: 1

Compilation date: 27/05/2015

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** MAXCERAM 400 – HEAVY DUTY EPOXY CERAMIC REBUILDING COMPOUND ACTIVATOR BASE

**Product code:** MAXCERAM 400 – HEAVY DUTY EPOXY CERAMIC REBUILDING COMPOUND ACTIVATOR BASE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** MaxKote

Sherburn in Elmet

Leeds

North Yorkshire

LS256BH

United Kingdom

**Tel:** 01977 682 903

**Email:** [info@MaxKote.co.uk](mailto:info@MaxKote.co.uk)

#### 1.4. Emergency telephone number

**Emergency tel:** 01977 682 903

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CHIP:** Xi: R36/38; Sens.: R43; N: R51/53

**Classification under CLP:** Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

**Most important adverse effects:** Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### 2.2. Label elements

**Label elements:**

**Hazard statements:** H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

**Signal words:** Warning

**Hazard pictograms:** GHS07: Exclamation mark

GHS09: Environmental



[cont...]

## SAFETY DATA SHEET

MAXCERAM 400 – HEAVY DUTY EPOXY CERAMIC  
REBUILDING COMPOUND ACTIVATOR BASE

Page: 2

**Precautionary statements:** P102: Keep out of reach of children.  
P261: Avoid breathing vapours.  
P264: Wash skin thoroughly after handling.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+313: If skin irritation or rash occurs: Get medical advice/attention.  
P501: Dispose of contents/container to hazardous or special waste collection point.

### Label elements under CHIP:

**Hazard symbols:** Irritant.  
Dangerous for the environment.



**Risk phrases:** R36/38: Irritating to eyes and skin.  
R43: May cause sensitisation by skin contact.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S2: Keep out of the reach of children.  
S24: Avoid contact with skin.  
S29: Do not empty into drains.  
S37: Wear suitable gloves.  
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

BISPHENOL F TYPE EPOXY RESIN

| EINECS    | CAS        | CHIP Classification               | CLP Classification   | Percent |
|-----------|------------|-----------------------------------|--|---------|
| 500-108-2 | 28064-14-4 | Xi: R36/38; N: R51/53; Sens.: R43 | Skin Irrit. 2: H315; Eye Irrit. 2: H319;<br>Skin Sens. 1: H317; Aquatic Chronic 2:<br>H411 | 10-30%  |

[cont...]

## SAFETY DATA SHEET

MAXCERAM 400 – HEAVY DUTY EPOXY CERAMIC  
REBUILDING COMPOUND ACTIVATOR BASE

Page: 3

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

|           |            |                                   |  |        |
|-----------|------------|-----------------------------------|--|--------|
| 500-033-5 | 25068-38-6 | Xi: R36/38; Sens.: R43; N: R51/53 | Eye Irrit. 2: H319; Skin Irrit. 2: H315;<br>Skin Sens. 1: H317; Aquatic Chronic 2:<br>H411 | 10-30% |
|-----------|------------|-----------------------------------|--|--------|

### Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

[cont...]

## SAFETY DATA SHEET

MAXCERAM 400 – HEAVY DUTY EPOXY CERAMIC  
REBUILDING COMPOUND ACTIVATOR BASE

Page: 4

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.  
Do not handle in a confined space. Avoid the formation or spread of dust in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

## Section 9: Physical and chemical properties

[cont...]

## SAFETY DATA SHEET

MAXCERAM 400 – HEAVY DUTY EPOXY CERAMIC  
REBUILDING COMPOUND ACTIVATOR BASE

Page: 5

### 9.1. Information on basic physical and chemical properties

**State:** Paste  
**Colour:** Various  
**Odour:** Barely perceptible odour  
**Evaporation rate:** Negligible  
**Oxidising:** Non-oxidising (by EC criteria)  
**Solubility in water:** Insoluble  
**Viscosity:** Highly viscous  
**Boiling point/range°C:** >200  
**Flash point°C:** >150  
**Relative density:** 2.1g/cc

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Toxicity values:**

| Route | Species | Test | Value | Units |
|-------|---------|------|-------|-------|
|-------|---------|------|-------|-------|

[cont...]

## SAFETY DATA SHEET

MAXCERAM 400 – HEAVY DUTY EPOXY CERAMIC  
REBUILDING COMPOUND ACTIVATOR BASE

Page: 6

|      |     |      |       |       |
|------|-----|------|-------|-------|
| ORAL | RAT | LD50 | >2000 | mg/kg |
| ORAL | RBT | LD50 | >2000 | mg/kg |

### Hazardous ingredients:

#### BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

|     |     |      |       |       |
|-----|-----|------|-------|-------|
| ORL | MUS | LD50 | 15600 | mg/kg |
| ORL | RAT | LD50 | 11400 | mg/kg |
| SKN | RBT | LD50 | >20   | ml/kg |

### Relevant effects for mixture:

| Effect        | Route   | Basis                 |
|---------------|---------|-----------------------|
| Irritation    | OPT DRM | Hazardous: calculated |
| Sensitisation | DRM     | Hazardous: calculated |

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicity values:

| Species | Test     | Value | Units |
|---------|----------|-------|-------|
| FISH    | 96H LC50 | >5000 | mg/l  |

### 12.2. Persistence and degradability

**Persistence and degradability:** Not biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** Bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Insoluble in water.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

[cont...]

## SAFETY DATA SHEET

MAXCERAM 400 – HEAVY DUTY EPOXY CERAMIC  
REBUILDING COMPOUND ACTIVATOR BASE

Page: 7

### 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 08 04 09

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN3077

### 14.2. UN proper shipping name

**Shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

### 14.3. Transport hazard class(es)

**Transport class:** 9

### 14.4. Packing group

**Packing group:** III

### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** Yes

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** E

**Transport category:** 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

## Section 16: Other information

[cont...]

## SAFETY DATA SHEET

MAXCERAM 400 – HEAVY DUTY EPOXY CERAMIC  
REBUILDING COMPOUND ACTIVATOR BASE

Page: 8

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

R36/38: Irritating to eyes and skin.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.