

M-CHEM 101 Chemical Resistant Epoxy Coating – Extended Cure BASE COMPONENT

Page: 1

Compilation date: 27/04/2020

Revision No: 3

#### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: M-CHEM 101 Chemical Resistant Epoxy Coating - Extended Cure

BASE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

Company name: MaxKote Limited

MaxKote Limited

Tower Court, Oakdale Road

Clifton Moor

York

**YO30 4XL** 

North Yorkshire

**Tel:** +44 (0) 1904 809 773

Email: info@maxkote.co.uk

#### 1.4. Emergency telephone number

Emergency tel: +44 (0) 1904 809 773

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/38; Sens.: R43; N: R51/53

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; -:

EUH205

Most important adverse effects: Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic

organisms, may cause long-term adverse effects in the aquatic environment.

#### 2.2. Label elements

### Label elements:

Hazard statements: EUH205: Contains epoxy constituents. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental

[cont...]

M-CHEM 101 Chemical Resistant Epoxy Coating – Extended Cure BASE COMPONENT





Precautionary statements: P102: Keep out of reach of children.

P273: Avoid release to the environment.
P264: Wash skin thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of contents/container to hazardous or special waste collection point.

Label elements under CHIP:

Hazard symbols: Irritant.

Dangerous for the environment.





Risk phrases: R36/38: Irritating to eyes and skin.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Safety phrases: S2: Keep out of the reach of children.

S24: Avoid contact with skin.S29: Do not empty into drains.S37: Wear suitable gloves.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

### 2.3. Other hazards

## Section 3: Composition/information on ingredients

PBT: This product is not identified as a PBT/vPvB substance.

### 3.2. Mixtures

### Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS CAS CHIP Classification CLP Classification Percent	EINECS	CAS	CHIP Classification	CLP Classification	Percent
---	--------	-----	---------------------	--------------------	---------

Page: 2

M-CHEM 101 Chemical Resistant Epoxy Coating – Extended Cure BASE COMPONENT

Page: 3

500-033-5	25068-38-6	Xi: R36/38; Sens.: R43; N: R51/53	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%
BISPHENOL F	TYPE EPOXY R	ESIN		
500-108-2	28064-14-4	Xi: R36/38; N: R51/53; Sens.: R43	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%
OXIRANE, MO	ONO[(C12-14ALK	YLOXY)METHYL] DERIVATIVES		
271-846-8	68609-97-2	Xi: R38; Sens.: R43	Skin Irrit. 2: H315; Skin Sens. 1: H317	1-10%

#### Section 4: First aid measures

### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Not applicable.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.Ingestion: There may be irritation of the throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Not applicable.

## 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Dry chemical powder. Carbon dioxide.

# 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** W ear self-contained breathing apparatus.

#### Section 6: Accidental release measures

M-CHEM 101 Chemical Resistant Epoxy Coating – Extended Cure BASE COMPONENT

Page: 4

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

#### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method. Refer to section 13 of SDS for suitable method of disposal.

#### 6.4. Reference to other sections

#### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct

sunlight. Avoid incompatible materials and conditions - see section 10 of SDS.

Suitable packaging: Must only be kept in original packaging.

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

#### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

Workplace exposure limits: No data available.

## **DNEL/PNEC Values**

#### 8.2. Exposure controls

**DNEL / PNEC** No data available.

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Respiratory protection not required.

Hand protection: Protective gloves.Eye protection: Safety glasses.

**Skin protection:** Impermeable protective clothing.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

### Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid

M-CHEM 101 Chemical Resistant Epoxy Coating – Extended Cure BASE COMPONENT

Page: 5

Colour: Various

Odour: Barely perceptible odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: >200 Flash point°C: >150

Relative density: 1.75g/cc

### 9.2. Other information

Other information: No data available.

#### Section 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

## 10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Flames.

## 10.5. Incompatible materials

Materials to avoid: Strong acids. Strong oxidising agents. Amines. Alkalis.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

## **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

### **Toxicity values:**

Route	Species	Test	Value	Units
ORAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

M-CHEM 101 Chemical Resistant Epoxy Coating – Extended Cure BASE COMPONENT

Page: 6

## **Hazardous ingredients:**

## **BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}**

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

## OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES

ORL	RAT	LD50	17100	mg/kg	

#### Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Not applicable.

### **Section 12: Ecological information**

## 12.1. Toxicity

### **Ecotoxicity values:**

Species	Test	Value	Units
FISH	96H LC50	2	mg/l

#### 12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

# 12.4. Mobility in soil

Mobility: Insoluble in water.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

M-CHEM 101 Chemical Resistant Epoxy Coating – Extended Cure BASE COMPONENT

Page: 7

#### 12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

#### Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company. Mixed material, once fully cured, can be disposed as solid waste.

Waste code number: 08 04 09

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

#### **Section 14: Transport information**

#### 14.1. UN number

UN number: UN3082

#### 14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT})

#### 14.3. Transport hazard class(es)

Transport class: 9

### 14.4. Packing group

## 14.5. Environmental hazards

Packing group: III

Environmentally hazardous: Yes Marine pollutant: Yes

#### 14.6. Special precautions for user

Tunnel code: E

Transport category: 3

#### Section 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

### Section 16: Other information

M-CHEM 101 Chemical Resistant Epoxy Coating – Extended Cure BASE COMPONENT

Page: 8

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/

83.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH205: Contains epoxy constituents. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

R36/38: Irritating to eyes and skin.

R38: Irritating to skin.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.