

## SAFETY DATA SHEET

M-CERAM 501 EPOXY CERAMIX HIGH TEMPERATURE & ACID  
RESISTANT COATING - BASE

Page: 1

Compilation date: 02/09/2019

Revision No: 3

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** M-CERAM 501 EPOXY CERAMIX HIGH TEMPERATURE & ACID RESISTANT COATING - BASE

**Product code:** M-CERAM 501

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Maxkote Limited

Tower Court, Oakdale Road  
Clifton Moor  
Yorks  
North Yorkshire  
YO30 4XL  
United Kingdom

**Tel:** 01904 809 773

**Email:** [info@MaxKote.co.uk](mailto:info@MaxKote.co.uk)

#### 1.4. Emergency telephone number

**Emergency tel:** 01904 809 773

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CHIP:** Xn: R20; Xn: R40

**Classification under CLP:** Eye Irrit. 2: H319; Aquatic Chronic 2: H411; Carc. 2: H351; Skin Irrit. 2: H315; Skin Sens. 1: H317

**Most important adverse effects:** Harmful by inhalation. Limited evidence of a carcinogenic effect.

#### 2.2. Label elements

##### Label elements:

**Hazard statements:** H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H351: Suspected of causing cancer.

H411: Toxic to aquatic life with long lasting effects.

**Signal words:** Warning

**Hazard pictograms:** GHS07: Exclamation mark

GHS08: Health hazard

GHS09: Environmental

[cont...]

**SAFETY DATA SHEET**  
M-CERAM 501 EPOXY CERAMIX HIGH TEMPERATURE & ACID  
RESISTANT COATING - BASE



**Precautionary statements:** P202: Do not handle until all safety precautions have been read and understood.  
P273: Avoid release to the environment.  
P261: Avoid breathing vapours.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+313: IF exposed or concerned: Get medical attention.  
P333+313: If skin irritation or rash occurs: Get medical advice/attention.  
P501: Dispose of contents/container to hazardous or special waste collection point.

**Label elements under CHIP:**

**Hazard symbols:** Harmful.



**Risk phrases:** R20: Harmful by inhalation.  
R40: Limited evidence of a carcinogenic effect.

**Safety phrases:** S2: Keep out of the reach of children.  
S36/37: Wear suitable protective clothing and gloves.  
S46: If swallowed, seek medical advice immediately and show this container or label.

**2.3. Other hazards**

**PBT:** This product is not identified as a PBT/vPvB substance.

**Section 3: Composition/information on ingredients**

**3.2. Mixtures**

**Hazardous ingredients:**

EPOXY PHENOL NOVOLAC RESIN

EINECS	CAS	CHIP Classification	CLP Classification	Percent
500-108-2	28064-14-4	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%

**SAFETY DATA SHEET**  
M-CERAM 501 EPOXY CERAMIX HIGH TEMPERATURE & ACID  
RESISTANT COATING - BASE

Page: 3

FURFURYL ALCOHOL

202-626-1	98-00-0	Xn: R40; T: R23; Xn: R21/22; Xn: R48/20; Xi: R36/37	Carc. 2: H351; Acute Tox. 3: H331; Acute Tox. 4: H312; Acute Tox. 4: H302; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335	1-10%
-----------	---------	---	---	-------

#### Section 4: First aid measures

##### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

##### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

##### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

#### Section 5: Fire-fighting measures

##### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

##### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

##### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

#### Section 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the

[cont...]

**SAFETY DATA SHEET**  
M-CERAM 501 EPOXY CERAMIX HIGH TEMPERATURE & ACID  
RESISTANT COATING - BASE

Page: 4

contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of dust in the air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**FURFURYL ALCOHOL**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	20 mg/m3	61 mg/m3	-	-

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

**Hand protection:** Protective gloves.

[cont...]

**SAFETY DATA SHEET**  
M-CERAM 501 EPOXY CERAMIX HIGH TEMPERATURE & ACID  
RESISTANT COATING - BASE

Page: 5

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Paste

**Colour:** Dark grey

**Odour:** Characteristic odour

**Evaporation rate:** Negligible

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Insoluble

**Viscosity:** Viscous

**Boiling point/range°C:** No data available.

**Flash point°C:** 60 - 93

**Relative density:** 2.6g/cc

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

[cont...]

**SAFETY DATA SHEET**  
M-CERAM 501 EPOXY CERAMIX HIGH TEMPERATURE & ACID  
RESISTANT COATING - BASE

Page: 6

**Toxicity values:**

Route	Species	Test	Value	Units
ORAL	RAT	LD50	>2000	mg/kg
ORAL	RBT	LD50	>2000	mg/kg

**Hazardous ingredients:**

**FURFURYL ALCOHOL**

ORL	MUS	LD50	338	mg/kg
ORL	RAT	LD50	460	mg/kg
SKN	RAT	LD50	3825	mg/kg

**Relevant effects for mixture:**

Effect	Route	Basis
Acute toxicity (harmful)	INH	Hazardous: calculated

**Symptoms / routes of exposure**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:**

Species	Test	Value	Units
FISH	96H LC50	>5000	mg/l

**12.2. Persistence and degradability**

**Persistence and degradability:** Biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

**12.4. Mobility in soil**

**Mobility:** Readily absorbed into soil.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

[cont...]

**SAFETY DATA SHEET**  
M-CERAM 501 EPOXY CERAMIX HIGH TEMPERATURE & ACID  
RESISTANT COATING - BASE

Page: 7

**12.6. Other adverse effects**

**Other adverse effects:** Negligible ecotoxicity.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 08 04 09

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN3077

**14.2. UN proper shipping name**

**Shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.  
(EPOXY PHENOL NOVOLAC RESIN)

**14.3. Transport hazard class(es)**

**Transport class:** 9

**14.4. Packing group**

**Packing group:** III

**14.5. Environmental hazards**

**Environmentally hazardous:** Yes

**Marine pollutant:** No

**14.6. Special precautions for user**

**Special precautions:** No special precautions.

**Tunnel code:** E

**Transport category:** 3

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Specific regulations:** Not applicable.

**15.2. Chemical Safety Assessment**

**Section 16: Other information**

[cont...]

**SAFETY DATA SHEET**  
M-CERAM 501 EPOXY CERAMIX HIGH TEMPERATURE & ACID  
RESISTANT COATING - BASE

Page: 8

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H302: Harmful if swallowed.  
H312: Harmful in contact with skin.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H331: Toxic if inhaled.  
H335: May cause respiratory irritation.  
H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H411: Toxic to aquatic life with long lasting effects.  
R20: Harmful by inhalation.  
R21/22: Harmful in contact with skin and if swallowed.  
R23: Toxic by inhalation.  
R36/37: Irritating to eyes and respiratory system.  
R40: Limited evidence of a carcinogenic effect.  
R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.