

M-CHEM 401 ACID RESISTANT HIGH TEMPERATURE COATING EXTENDED CURE - BASE

Page: 1 Compilation date: 10/12/2018

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

# Product name: RESICHEM 512 UCEN 90 XL BASE COMPONENT

Product code: 512 XL

1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Company name: Maxkote Limited

Tower Court, Oakdale Road Clifton Moor Yorks North Yorkshire YO30 4XL United Kingdom

Tel: +44 (0) 1904 809 773 Email: info@maxkote.co.uk

# 1.4. Emergency telephone number

Emergency tel: +44 (0) 1904 809 773

### Section 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; -:

EUH205

Classification under CHIP: This product has no classification under CHIP.

#### 2.2. Label elements

#### Label elements:

Hazard statements:	EUH205: Contains epoxy constituents. May produce an allergic reaction.
	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
	H411: Toxic to aquatic life with long lasting effects.
Signal words:	Warning
Hazard pictograms:	GHS07: Exclamation mark
	GHS09: Environmental
	$\wedge \wedge$



# M-CHEM 401 ACID RESISTANT HIGH TEMPERATURE COATING EXTENDED CURE - BASE

	•
Precautionary statements:	P102: Keep out of reach of children.
	P264: Wash skin thoroughly after handling.
	P273: Avoid release to the environment.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P302+352: IF ON SKIN: Wash with plenty of water/.
	P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P333+313: If skin irritation or rash occurs: Get medical advice/attention.
	P501: Dispose of contents/container to hazardous or special waste collection point.
2.3 Other hazards	

2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

3.2. Mixtures

# Hazardous ingredients:

### EPOXY PHENOL NOVOLAC RESIN

EINECS	CAS	CHIP Classification	CLP Classification	Percent
500-108-2	28064-14-4	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411	70-90%

# Section 4: First aid measures

4.1. Description of first aid me	4.1. Description of first aid measures			
Skin contact:	Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash			
	immediately with plenty of soap and water.			
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.			
Ingestion: Wash out mouth with water. Consult a doctor.				
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a				
	doctor.			
4.2. Most important symptoms	s and effects, both acute and delayed			
Skin contact:	There may be irritation and redness at the site of contact.			
Eye contact:	There may be irritation and redness. The eyes may water profusely.			
Ingestion:	There may be soreness and redness of the mouth and throat.			
Inhalation:	Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may			
	cause coughing or wheezing.			
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.			

Page: 2

## M-CHEM 401 ACID RESISTANT HIGH TEMPERATURE COATING EXTENDED CURE - BASE

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

#### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: W ear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

# Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

#### Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

**Suitable packaging:** Must only be kept in original packaging.

### M-CHEM 401 ACID RESISTANT HIGH TEMPERATURE COATING EXTENDED CURE - BASE

Page: 4

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

#### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

Workplace exposure limits: No data available.

#### **DNEL/PNEC** Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be

impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Barely perceptible odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Viscous

Boiling point/range°C: >35

Relative density: 1.4g/cc

Flash point°C: >93

#### 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## M-CHEM 401 ACID RESISTANT HIGH TEMPERATURE COATING EXTENDED CURE - BASE

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

# 10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### **10.6. Hazardous decomposition products**

Haz. decomp. products: In combustion emits toxic fumes.

### Section 11: Toxicological information

## 11.1. Information on toxicological effects

**Toxicity values:** 

Route	Species	Test	Value	Units
ORAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

12.1. Toxicity

#### **Ecotoxicity values:**

Species	Test	Value	Units
FISH	96H LC50	>5000	mg/l

### 12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

### M-CHEM 401 ACID RESISTANT HIGH TEMPERATURE COATING EXTENDED CURE - BASE

## 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

# 12.5. Results of PBT and vPvB assessment

#### **PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

#### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Waste code number: 08 04 09

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

regulations regarding disp

# Section 14: Transport information

# 14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

### (EPOXY PHENOL NOVOLAC RESIN)

#### 14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

## Section 15: Regulatory information

Marine pollutant: Yes

## M-CHEM 401 ACID RESISTANT HIGH TEMPERATURE COATING EXTENDED CURE - BASE

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

# 15.2. Chemical Safety Assessment

# **Section 16: Other information**

# Other information

 Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No
 453/2010.

 \* indicates text in the SDS which has changed since the last revision.

 Phrases used in s.2 and s.3:
 EUH205: Contains epoxy constituents. May produce an allergic reaction.

 H315: Causes skin irritation.
 H317: May cause an allergic skin reaction.

 H319: Causes serious eye irritation.
 H411: Toxic to aquatic life with long lasting effects.

 Legal disclaimer:
 The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.