Revision date: 23/10/2018 revision 3



# SAFETY DATA SHEET

# M-CORR 300 HIGH BUILD SOLVENT FREE PU COATING - ACTIVATOR

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name M-CORR 300 HIGH BUILD SOLVENT FREE PU COATING - ACTIVATOR

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Uses advised against**No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier MaxKote Ltd

Tower Court, Oakdale Road, Clifton Moor

York

North Yorkshire

**YO30 4XL** 

United Kingdom

info@maxkote.co.uk

emergency number: +440904 809 773

1.4. Emergency telephone number

# SECTION 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Resp. Sens. 1 - H334 Skin Sens. 1

- H317 Carc. 2 - H351 STOT SE 3 - H335 STOT RE 2 - H373

Environmental hazards Not Classified

**Classification (67/548/EEC or** Xn;R20,R48/20. Carc. Cat. 3;R40. R42/43. Xi;R36/37/38. **1999/45/EC)** 

2.2. Label elements

**Pictogram** 





Signal word Danger

# M-CORR 300 HIGH BUILD SOLVENT FREE PU COATING -

### **ACTIVATOR**

**Hazard statements** H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer by inhalation.

H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements** EUH204 Contains isocyanates. May produce an allergic reaction.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

Contains DIPHENYLMETHANE -4, 4'- DI-ISOCYANATE, Homopolymer of methylenediphenyl

diisocyanate, Isocyanic Acid, polymethylenepolyphenylene ester

Supplementary precautionary

statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe vapour/spray. P261 Avoid breathing vapour/spray.

P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in

a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/doctor if you feel unwell.

P313 Get medical advice/attention.

P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 If eye irritation persists:

P362 Take off contaminated clothing.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container to ...

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

# SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

# M-CORR 300 HIGH BUILD SOLVENT FREE PU COATING -**ACTIVATOR**

Homopolymer of methylenediphenyl diisocyanate

30-60%

CAS number: 39310-05-9 EC number: 500-297-1 REACH registration number: 01-

2119457013-49-0000

Xn;R20,R48/20. Carc. Cat. 3;R40. Xi;R36/37/38. R42/43.

Classification

Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 2 - H330

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319

Resp. Sens. 1 - H334 Skin Sens. 1 - H317

Carc. 2 - H351

STOT SE 3 - H335

STOT RE 2 - H373

Isocyanic Acid, polymethylenepolyphenylene ester

30-60%

CAS number: 9016-87-9

Classification

Classification (67/548/EEC or 1999/45/EC)

Xn;R20,R48/20. Carc. Cat. 3;R40. Xi;R36/37/38. R42/43.

Acute Tox. 4 - H332

Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

Resp. Sens. 1 - H334 Skin Sens. 1 - H317

Carc. 2 - H351

STOT SE 3 - H335

STOT RE 2 - H373

DIPHENYLMETHANE -4, 4'- DI-ISOCYANATE

10-30%

CAS number: 101-68-8

EC number: 202-966-0

Classification

Acute Tox. 4 - H332

Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

Resp. Sens. 1 - H334 Skin Sens. 1 - H317

Carc. 2 - H351

STOT SE 3 - H335

STOT RE 2 - H373

Classification (67/548/EEC or 1999/45/EC)

Carc. Cat. 3;R40 Xn;R20,R48/20 Xi;R36/37/38 R42/43

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

# SECTION 4: First aid measures

### 4.1. Description of first aid measures

**General information** 

Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

# M-CORR 300 HIGH BUILD SOLVENT FREE PU COATING -

#### **ACTIVATOR**

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place. In the event of any

sensitisation symptoms developing, ensure further exposure is avoided.

Ingestion Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water

or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing

such as collar, tie or belt.

Skin contact It is important to remove the substance from the skin immediately. In the event of any

sensitisation symptoms developing, ensure further exposure is avoided. Remove

contamination with soap and water or recognised skin cleansing agent. Get medical attention

if symptoms are severe or persist after washing.

**Eye contact** Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. If it is

suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth

resuscitation.

### 4.2. Most important symptoms and effects, both acute and delayed

**General information** See Section 11 for additional information on health hazards. The severity of the symptoms

described will vary dependent on the concentration and the length of exposure.

Inhalation May cause sensitisation or allergic reactions in sensitive individuals. A single exposure may

cause the following adverse effects: Headache. Exhaustion and weakness. Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.

**Ingestion** May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.

Prolonged or repeated exposure may cause the following adverse effects: Suspected of

causing cancer.

**Skin contact** May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to

skin. Prolonged or repeated exposure may cause the following adverse effects: Suspected of

causing cancer.

Eye contact Irritating to eyes.

# 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.

# SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry

powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

# M-CORR 300 HIGH BUILD SOLVENT FREE PU COATING - ACTIVATOR

# Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

This product is toxic.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Toxic

gases or vapours.

### 5.3. Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

#### SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

### Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid inhalation of dust and vapours. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes.

### 6.2. Environmental precautions

**Environmental precautions** 

Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

### 6.3. Methods and material for containment and cleaning up

## Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Provide adequate ventilation. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

# 6.4. Reference to other sections

# M-CORR 300 HIGH BUILD SOLVENT FREE PU COATING - ACTIVATOR

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. See Section 12 for additional information on ecological hazards. For waste disposal,

see Section 13.

# SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in

Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Suspected of causing cancer. Do not handle until all safety precautions have been read and understood. Do not handle broken packages

without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in accordance with local regulations. Keep only in the original container. Keep container

tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The

storage area floor should be leak-tight, jointless and not absorbent.

Storage class Toxic storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

# SECTION 8: Exposure Controls/personal protection

# 8.1. Control parameters

### Occupational exposure limits

# Homopolymer of methylenediphenyl diisocyanate

Long-term exposure limit (8-hour TWA): WEL 0.02 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 0.07 mg/m<sup>3</sup>

Sen as NCO

Isocyanic Acid, polymethylenepolyphenylene ester

Long-term exposure limit (8-hour TWA): WEL  $0.02~mg/m^3$  Short-term exposure limit (15-minute): WEL  $0.07~mg/m^3$ 

Skin sensitiser.

as NCO

#### DIPHENYLMETHANE -4, 4'- DI-ISOCYANATE

Long-term exposure limit (8-hour TWA): WEL 0,01 mg/m³ Short-term exposure limit (15-minute): WEL 0,07 mg/m³ as NCO

Sen

WEL = Workplace Exposure Limit

Sen = Capable of causing occupational asthma.

Homopolymer of methylenediphenyl diisocyanate (CAS: 39310-05-9)

# M-CORR 300 HIGH BUILD SOLVENT FREE PU COATING - ACTIVATOR

Ingredient comments EH40/2005 Workplace exposure limits. Medical supervision of all employees who

come into contact with respiratory sensitisers is recommended. Personnel with a history of asthma-type conditions, bronchitis or skin sensitisation conditions should not work with MDI based products. The OELs listed do not apply to previously sensitised individuals. Sensitised individuals should be removed from any further

exposure.

Biological limit values Predicted Effect Levels: No PECs available, Predicted Effect Levels: No PECs

available, Predicted Effect Levels: No PECs available Derivied Effect Levels: No DELs available Derivied Effect Levels: No DELs available Derivied Effect Levels:

No DELs available

### 8.2. Exposure controls

Protective equipment

# Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

## Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

# Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

### Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

#### Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

# M-CORR 300 HIGH BUILD SOLVENT FREE PU COATING -

**ACTIVATOR** 

**Environmental exposure** 

controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and Chemical Properties**

## 9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Colourless.

### 9.2. Other information

### SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

No potentially hazardous reactions known.

10.4. Conditions to avoid

**Conditions to avoid** There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

# 10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

### SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) Acute Tox. 4 - H332 Harmful if inhaled.

1.5

ATE inhalation (gases ppm) 22,727.27

ATE inhalation (vapours mg/l) 55.56

ATE inhalation (dusts/mists

Î

mg/l)

Skin corrosion/irritation

Revision date: 23/10/2018

Animal data

Irritating.

# M-CORR 300 HIGH BUILD SOLVENT FREE PU COATING - ACTIVATOR

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

**Respiratory sensitisation**There is evidence that the product can cause respiratory hypersensitivity.

Skin sensitisation

**Skin sensitisation** May cause skin sensitisation or allergic reactions in sensitive individuals.

Germ cell mutagenicity

**Genotoxicity - in vitro**Based on available data the classification criteria are not met.

Carcinogenicity

**Carcinogenicity** Suspected of causing cancer.

**IARC carcinogenicity**None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 3 - H335 May cause respiratory irritation.

Target organs Respiratory system, lungs

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

General information May cause cancer after repeated exposure. Risk of cancer depends on duration and level of

exposure. The severity of the symptoms described will vary dependent on the concentration

and the length of exposure.

Inhalation May cause sensitisation or allergic reactions in sensitive individuals. A single exposure may

cause the following adverse effects: Headache. Exhaustion and weakness.

**Ingestion** May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.

**Skin contact** May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to

skin.

Eye contact Irritating to eyes.

Route of entry Ingestion Inhalation Skin and/or eye contact

Target organs Respiratory system, lungs

**Medical considerations** Skin disorders and allergies.

# SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have

hazardous effects on the environment.

### 12.1. Toxicity

# M-CORR 300 HIGH BUILD SOLVENT FREE PU COATING - ACTIVATOR

**Toxicity** Based on available data the classification criteria are not met.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

Other adverse effects None known.

### SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners

may retain some product residues and hence be potentially hazardous.

**Disposal methods**Dispose of surplus products and those that cannot be recycled via a licensed waste disposal

contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

Incineration or landfill should only be considered when recycling is not feasible.

## **SECTION 14: Transport information**

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

# M-CORR 300 HIGH BUILD SOLVENT FREE PU COATING - ACTIVATOR

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EH40/2005 Workplace exposure limits.

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 453/2010 of 20 May 2010.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended)

Dangerous Preparations Directive 1999/45/EC. Dangerous Substances Directive 67/548/EEC.

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## <u>Inventories</u>

## **EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

### SECTION 16: Other information

Classification procedures according to Regulation (EC)

Acute Tox. 4 - H332: STOT RE 2 - H373: STOT SE 3 - H335: Skin Irrit. 2 - H315: Eye Irrit. 2 - H319: Resp. Sens. 1 - H334: Skin Sens. 1 - H317: Carc. 2 - H351: : Calculation method.

1272/2008

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this

material.

Revision date 16/05/2013

Risk phrases in full R20 Harmful by inhalation.

R36/37/38 Irritating to eyes, respiratory system and skin.

R40 Limited evidence of a carcinogenic effect.

R42/43 May cause sensitisation by inhalation and skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

# M-CORR 300 HIGH BUILD SOLVENT FREE PU COATING - ACTIVATOR

Hazard statements in full H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H351 Suspected of causing cancer by inhalation.

H373 May cause damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.